



SALFORD FIELD CULTIVATORS

Built for strength, durability and performance. Unique features like hydraulic self-leveling and the land hugger fully floating frame set Salford field cultivators apart.



HEAVY DUTY FRAME

Salford cultivators are the complete package. A heavy-duty frame provides longevity to these machines and mounting options to complete the finishing packages on the cultivators. Unlike many competitors that only carry either harrow or baskets. Salford cultivators have both



HYDRAULIC SELF-LEVELING FRAME

The self-leveling frame sections of Salford cultivators follow ground contours exceptionally well. The unique frame design allows cultivators to remain level front to back and section to section as the machine follows ground undulations, providing reliable results in varying conditions.



TANDEM AXLES

Found on all Salford cultivators' mainframe, primary wing, and secondary wings. The tandems ensure that shovels on each cultivator section run at even depth as the cultivator crosses uneven ground, providing exceptionally consistent results.

LAND HUGGER FLOATING FRAME

Available on field cultivators 40 ft. and over, the Land Hugger fully floating frame provides precise depth control in rolling terrain.

LAND HUGGER IN THE FIELD - During field operation the cultivator's tongue is able to flex up and down, keeping the machine level in the field.

LAND HUGGER ON THE ROAD - When the Land Hugger frame is raised into transport position the tongue automatically locks in place for safer towing.

3 model types range in size from 19 feet to 62 feet and can be equipped with standard S-Tines, higher clearance 2 piece S-Tines or heavy C-Shanks*

Standard Harrow Options

450, 550 & 700-

- FULLY LOADED FEATURE SET
 Single point hydraulic depth control, hydraulic self-leveling frame and walking tandems are all standard features on Salford field cultivators. Add heavy duty tow hitches for your packer.
- ENGINEERED FOR A LIFETIME OF SERVICE
 Built with oversized frames, axles and hinge points for years of dependable service and less down time.
- S-TINE FIELD CULTIVATORS

 20-inch under frame clearance with 4.5 inch spacing and Long
 Life cast shovel. 110 lbs 200 lbs operating pressure*.
- 2 PIECE S-TINE FIELD CULTIVATORS
 26-inch under frame clearance with 4.5 inch spacing and long life cast shovel. 110 lbs 200 lbs operating pressure*.
- C-SHANK FIELD CULTIVATORS

 26-inch under frame clearance with 7 inch spacing (9 inch spacing on select models only) and replaceable nylon pivot bushing for worry free operation with no greasing. 200 lbs 270 lbs. adjustable operating pressure*.

*Not all shank and shank spacing options are available in every model size.












* 3/8 in. 2 Bar Tine Double 11 in. rolling harrow and not available on C-Shank models



OPERATING DEPTH OPERATING SPEED (MPH) SEED BED PREPARATION FIELD LEVELING CHEMICAL/FERTILIZER **INCORPORATION RESIDUE MANAGEMENT**

WEED CONTROL

REMOVAL

SURFACE COMPACTION

s-tine model ¬ ┌ 1.5 - 4 in. 5.5-9 20-30 Excellent Excellent Excellent Excellent Average Excellent

2-piece s-tine model 2 - 4 in. 4.5-7 40-50 Excellent Excellent Excellent Excellent Good Excellent





FIELD CULTIVATORS MODEL SPECS

450 FIELD CULTIVATORS

Working Width	S-Tine Number of tines 4.5 in.	2-Piece S-Tine Number of tines 4.5 in.	C-Shank Number of tines 7 in.	Transport Width (Approx.)	Transport Height (Approx.)	H.P. Required
19 ft.	52	52	33	12 ft. 9 in.	11 ft. 5 in.	95 - 115
21 ft.	56	56	37	12 ft. 9 in.	12 ft. 3 in.	100 - 125
23 ft.	60	60	39	12 ft. 9 in.	13 ft.	115 - 140
25 ft.	66	66	43	12 ft. 9 in.	13 ft. 8 in.	125 - 150

550 FIELD CULTIVATORS

Working Width	S-Tine Number of tines 4.5 in.	2-Piece S-Tine Number of tines 4.5 in.	C-Shank Number of tines 7 in.	Transport Width (Approx.)	Transport Height (Approx.)	H.P. Required	
28 ft.	76	76	49	15 ft. 3 in.	12 ft. 10 in.	140 - 170	
30 ft.	80	80	51	16 ft. 4 in.	14 ft.2 in.	150 - 180	
32 ft.	86	86	55	18 ft. 4 in.	13 ft. 10 in.	160 - 190	
40 ft.*	108	108	69	18 ft. 11 in.	12 ft. 3 in.	200 - 240	
v -							

*Bi-fold frame

700 FIELD CULTIVATORS

Working Width	S-Tine Number of tines 4.5 in.	2-Piece S-Tine Number of tines 4.5 in.	C-Shank Number of tines 7 in.	C-Shank Number of tines 9 in.	Transport Width (Approx.)	Transport Height (Approx.)	H.P. Required
40 ft.	-	-	68	54	20 ft. 2 in.	15 ft. 10 in.	210 - 250
44 ft.*	116	116	75	58	18 ft. 11 in.	14 ft.4 in.	220 - 260
50 ft.*	132	132	85	66	18 ft. 11 in.	14 ft. 4 in.	250 - 300
62 ft.*	164	164	102	82	20 ft. 11 in.	15 ft. 6 in.	310 - 400

*Bi-fold frame















See our full line of products and find your local dealer at salfordgroup.com or call 1-866-442-1293

Products and specifications subject to change without notice and without liability therefore. Images may include optional equipment. Salford® is a registered trademark of Salford Group Inc. Copyright©2024 Salford Group Inc. 2024.08 # 10108968 - LITERATURE, SALFORD, CULTIVATORS.





